



Clorox Professional Products Company
 1221 Broadway
 Oakland, CA 94612
 Tel. (510) 271-7000

Material Safety Data Sheet

I Product: CLOROX COMMERCIAL SOLUTIONS® GREEN WORKS™ NATURALLY DERIVED NEUTRAL FLOOR CLEANER – USER-PREPARED READY-TO-USE SOLUTION (1:64 DILUTION RATE)														
Description: CLEAR, COLORLESS, THIN LIQUID WITH LEMON SCENT														
Other Designations	Distributor	Emergency Telephone Nos.												
	The Clorox Sales Company 1221 Broadway Oakland, CA 94612	For Medical Emergencies call: 1-800-446-1014 For Transportation Emergencies, call Chemtrec: 1-800-424-9300												
II Health Hazard Data		III Hazardous Ingredients												
<p>May cause minor eye and skin irritation. No medical conditions are known to be aggravated by exposure to this product.</p> <p>FIRST AID:</p> <p>EYE CONTACT: Immediately rinse with plenty of water. If irritation persists, call a doctor.</p> <p>INGESTION: Drink a glassful of water. Call a doctor or poison control center.</p> <p>SKIN CONTACT: Rinse with plenty of water. If irritation persists, call a doctor.</p> <p>INHALATION: Remove to fresh air. If breathing problems develop, call a doctor.</p>		<table border="1"> <thead> <tr> <th>Ingredient</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Alkyl polyglucoside CAS # 68515-73-1</td> <td><1%</td> <td>not established</td> </tr> <tr> <td>Lauramine Oxide CAS # 1643-20-5</td> <td><1%</td> <td>not established</td> </tr> <tr> <td>Ethyl alcohol CAS # 64-17-5</td> <td><1%</td> <td>1000 ppm - TLV-TWA 1000 ppm – OSHA-PEL</td> </tr> </tbody> </table> <p>TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average OSHA-PEL = OSHA Permissible Exposure Limit - Time Weighted Average None of the materials in this product are on the IARC, OSHA, or NTP carcinogen lists.</p>	Ingredient	Concentration	Worker Exposure Limit	Alkyl polyglucoside CAS # 68515-73-1	<1%	not established	Lauramine Oxide CAS # 1643-20-5	<1%	not established	Ethyl alcohol CAS # 64-17-5	<1%	1000 ppm - TLV-TWA 1000 ppm – OSHA-PEL
Ingredient	Concentration	Worker Exposure Limit												
Alkyl polyglucoside CAS # 68515-73-1	<1%	not established												
Lauramine Oxide CAS # 1643-20-5	<1%	not established												
Ethyl alcohol CAS # 64-17-5	<1%	1000 ppm - TLV-TWA 1000 ppm – OSHA-PEL												
IV Special Protection and Precautions		V Transportation and Regulatory Data												
<p>No special protection or precautions have been identified for using this product under directed use conditions. The following recommendations are given for production facilities and for other conditions and situations where there is increased potential for accidental, large-scale or prolonged exposure.</p> <p>Hygienic Practices: Wash hands after direct contact. Do not wear product-contaminated clothing for prolonged periods.</p> <p>Engineering Controls: Use local exhaust to minimize exposure to product mist.</p> <p>Personal Protective Equipment: Wear safety glasses. Wear rubber or neoprene gloves if there is the potential for repeated or prolonged skin contact. In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.</p>		<p>DOT, IATA, IMDG: Not restricted.</p> <p>EPA - SARA Title III/CERCLA: This product is regulated under Sections 311/312. This product contains no chemicals which are regulated under Section 313 or regulated under Section 304/CERCLA.</p> <p>TSCA 8(b): All components of this product are either on the TSCA 8(b) inventory or otherwise exempt from listing.</p> <p>TSCA 12(b): This product is not subject to TSCA 12(b) reporting requirements.</p>												
VI Spill Procedures/Waste Disposal		VII Reactivity Data												
<p>Spill Procedures: Absorb and containerize. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.</p> <p>Waste Disposal: Dispose of in accordance with all applicable federal, state, and local regulations.</p>		Stable under normal use and storage conditions.												
VIII Fire and Explosion Data		IX Physical Data												
<p>Flash Point: >180°F (estimated, closed cup)</p> <p>Fire Extinguishing Agents: Dry chemical, carbon dioxide (CO₂), foam, or water spray.</p>		<p>pH (diluted solution; 1:64) 6 - 8</p> <p>Specific gravity ~1.0</p> <p>Solubility in water Soluble</p>												